

Ultra SCSI CardBus PC Card

CB31Pismo



Features

- Add Ultra-SCSI port to your PowerBookG3(Wallstreet 1988, Lombard1999), PowerBook500/400(Pismo, 2000) and PowerBookG4(Titanium).
- Get DeskTop performance and Ultra-SCSI speed up to 20MB/Sec.
- Supports Ultra-SCSI device and legacy SCSI device. HardDisk,CD-R/W,Scanner,FilmScanner,ORB,Jaz,and MO.
- Includes SCSI-2 Hi-Density 50P cable and HD50-C50 Adapter.
- Includes Disk formatter and Auto Mounter utility.
- Includes SCSI configuration Utility.
- Supports softRAID(softRAID,LLC.)
- Supports Ultra SCSI rates up to 20MB/sec.
- 32bit databus and 33MHz operation.
- Supports bus mastering data transfer.
- Ready for PowerManagement.
- Low power consumption.
- Supports scatter/gather and tagged queue.

System Requirements

-PowerBook G3/G4 with CardBus ready PC Card Slot.

- PowerBook G4(Titanium)
- PowerBook 500, 400 (2000 Pismo)
- PowerBook G3/400, G3/333 (1999 Lombard)
- PowerBook G3/300, G3/292, G3/266, G3/250, G3/233 (1998,Wallstreet)

-MacOS 8.6/ 9/ 9.0.2/9.0.4/9.1/9.2.x/X 10.1.x

Q. What is difference from CB31PB (Our former product)?

A. The only difference is bundled cable.

CB31PB

Hi-density 50pin cable
Centronics 50pin cable

CB31Pismo

Hi-density 50pin cable
Hi-Density 50F to Centronics 50M adapter.

Device List

[CD-R/W Drives]

- TEAC : CD-R56S, CD-R824S
- JVC : XR-S4224M
- Plextor : PX-412Ce, PX-R820
- YAMAHA : CDR400tk, CRW6416SX, CRW8424SX, CRW4416SX
- HP : CD-writer 9600se
- HP, Ricoh, Plextor, other Ultra-SCSI or SCSI CD-R/W drives.

[Film Scanner]

- Nikon : Coolscan III, Super CoolScan 2000, CoolScanIII LS-30
- Minolta : DimageScanMulti F-300
- Canon : FS2710
- Poraroid : SprintScan 4000

[Image Scanner]

- EPSON : Perfection 1200S, Expression 800, Expression 1600, GT-9600, GT-7000S, GT-7600S, GT-2200, ES-2000, ES-6000H
- Canon : CanoScan FB620S
- Microtec : ScanMakerX6
- UMAX : Mirage II, Mirage II Se, PowerLook 3000
- Agfa : Arcus II, Duoscan HiDHP

[MO Drive]

- Olympus : 640MO TURBO, 640MO TURBO LE, 640S II
- Fujitsu : SMB-640D2
- Mitsubishi : MK640KF, MK640KC, MK640LG

[Other Removable Media] iomega : JazV2000S, Zip250

Learn more at Certified Device list on www.ratocsystems.com/english/

Specifications

Data transfer rate	Up to 20MB/sec with Ultra SCSI devices Up to 10MB/sec with Fast SCSI devices
Termination type	Internal active termination provided
Operating requirements	CardBus PC Card slot Power Requirement - +3.3V - 130mA(idle), 300mA(MAX), 77mA(Power save mode) Temperature from 0°C to 55°C Relative humidity 20 to 80% (Non-condensing)
Package includes	- CB31 Ultra SCSI CardBus PC Card - Ultra SCSI cable with a Hi-Density 50pin connector(2feet) - Hi-Density 50F to Centronics 50M adapter - Software CD-ROM - CB31 driver - SCSI Configuration utility - B'sCrew Lite 3.1.1e CD-ROM - User's manual - Software License Agreement
Physical characteristicsP	54.0mm(W) x 85.6mm(L) x 5.0mm(H) (PC Card Standard Type II)

Windows is a trademark of Microsoft Corporation, registered in the U.S. and other countries. 'Mac', 'PowerMacintosh', Mac logo are registered trademarks of Apple Computers, Inc. registered in U.S. and other countries. 'PC Card', 'CardBus', PC Card logo and CardBus logo mark are registered trademarks of PCMCIA/JEITA. Other trademarks and logo are also registered trademark of each companies or organizations registered in U.S. and other countries.