

USB 1.1 Host Adaptor CF Card

CFU1U



**Add USB 1.1 Host downstream port
to your PDA**



**Expands your application and ideas
of PDA based systems**

► Features

- Add USB 1.1 Host downstream port to your PDA.
- Only one and first USB Host Adapter CF card in the world.
- Works on Compaq iPAQ and Dell Axim, expands your application and ideas of PDA based systems.
- Attach bar code scanners, magnetic stripe card readers, keypads or other USB HID devices.
- Supports USB Flash Memory reader/writers, USB Flash Memory sticks, Zip, Mo and other removable storage devices. Allows to save, restore big data from/to your PDA, to exchange big data simply with WindowsPC.
- Easy to install, fully compatible with Windows Microsoft ActiveSync.
- 100mA USB Bus-Power is available at the USB port, don't need AC adapters for Low-Power USB devices such as Keypads, Flash Memory reader/writers, Bar code scanners or USB Flash Memory sticks.
- Low power consumption allows a long battery life.

► System Requirements

One free CF TypeII compatible slot.

OS

- Pocket PC 2000 or Pocket PC 2002.

* ActiveSync and WindowsPC with CD-ROM drive are required to install the drivers into PDA.

► Certified PDA and USB devices

PDA

Compaq : iPAQ with CF Jacket, PC Card Jacket.

Dell : Axim

Fujitsu : Pocket Loox

USB device

HID class devices :

Keyboards, Bar code scanners, Magnetic stripe card readers, RF-ID tag readers

Mass Storage devices :

USB Flash memory stick, ZIP drive, Removable HDD, Flash Memory card reader/writers

► **Specifications**

Product name	USB 1.1 Host Adapter CF Card						
Product Number	CFU1U						
Bus Interface	CF+ and Compact Flash Specification Rev.1.4 compliant						
USB port interface	USB 1.1 compliant, supports Full(12Mbps) and Low(1.2Mbps).						
USB port Connector	Series A female (down stream).						
USB Bus-Power availability	100mA(5V) maximum.						
Physical Dimensions	CF TypeII 42.8(W) x 36.4(L) x 4.9(H) mm 1.69(W) x 1.43(L) x 0.13(H) inch						
Cable length	300mm(12 inch)						
Weights	CF Card : 10g. 0.35oz. Cable : 20g. 0.7oz.						
Power Consumption	<table border="1"> <tr> <td></td> <td>Standby</td> </tr> <tr> <td>5V Vcc</td> <td>27mA(Not included USB Bus power output current).</td> </tr> <tr> <td>3.3V Vcc</td> <td>34mA(Not included USB Bus power output current).</td> </tr> </table>		Standby	5V Vcc	27mA(Not included USB Bus power output current).	3.3V Vcc	34mA(Not included USB Bus power output current).
	Standby						
5V Vcc	27mA(Not included USB Bus power output current).						
3.3V Vcc	34mA(Not included USB Bus power output current).						
OS Support	Pocket PC 2000, Pocket PC 2002.						
Certification	VCCI/FCC Part 15, Class B.						
Warranty	Removable Cable 90 days, Card 5 years.						
Package includes	<ul style="list-style-type: none"> • CFU1 USB 1.1 Host Adapter CF card. • Removable cable. • Software CD-ROM < Software CD-ROM contents > -USB Host driver and INF file. -USB Device Class drivers(HID, MassStorage) For Pocket PC 2000 and Pocket PC 2002. • User's Guide 						

*Covered and licensed by U.S.patents 4,603,320 4,686,506 4,972,470.